Datasheet

PRODUCT	CAS20AA04A0	CAS20AB04A0	CAS20AC04A0	CAS20AD04A0	CAS20AA02A0	CAS20AB02A0	CAS20AC02A0	CAS20AD02A0
MAIN DRIVE								
CAPACITY - kgm(Nm)	2900 (28450)							
RATIO	1:1							
MAX. INPUT RPM	3500							
MAX. OUTPUT RPM								
AUXILIARY SERVICE OUTPUT - SIDE PTO								
MAX OUTPUT TORQUE - kgm(Nm)	122.32 (1200)				153.517 (1506)			
MAX KW	110 - (130 kW -Special)							
RATIO (*)	1.255:1				1:1 (Special)			
MAX. OUTPUT RPM	2500							
DISTANCE - mm (**)	328,5							
AUXILIARY SERVICE OUTPUT - HYDRAULIC SIDE PTO								
MAX OUTPUT TORQUE - kgm(Nm)	40.77 (400)							
MAX KW	35							
RATIO (#)	1.35:1 (1:1 to 1.6:1)							
MAX. OUTPUT RPM	2500							
DISTANCE - mm (***)	165							
OIL PUMP	OPT.							
OUTPUT TYPE	A	B	C	D	A	B	C	D
RPM COUNTER	OPT.							
TEMPERATURE SENSOR								
MATERIAL (CASE)	GH190 / ASTM A48 CLASS 30 / EN 1561-EN GJL 200 / DIN 1691 GG20							

: MAIN AXIS / AUXILIARY (HYDRAULIC SIDE PTO) AXIS.
For A Main Ratio Of 1:1, PLEASE CONTACT US TO LEARN ABOUT THE HYDRAULIC SIDE PTO RATIO.

A: CABIN SIDE SINGLE OUTPUT

B: CABIN SIDE DOUBLE OUTPUT

C: DIFFERENTIAL SIDE SINGLE OUTPUT

* : MAIN AXIS / AUXILIARY (SECOND) AXIS

** : DISTANCE BETWEEN THE FIRST AUXILIARY AXIS AND SECOND AUXILIARY AXIS

*** : DISTANCE BETWEEN THE MAIN AXIS AND AUXILIARY (HYDRAULIC SIDE PTO) AXIS

D: DIFFERENTIAL SIDE DOUBLE OUTPUT

OPT. : OPTIONAL

S: STANDARD

caseindustrygroup.com
gucaktarim.caseindustrygroup.com

2024 – ANKARA

"Pioneer Of Innovative Technology"

CASE INDUSTRY GROUP A.Ş.
Pioneer of Innovative Technology

TD.414.CAS20A.0010/AA